

Bitzer 4N.2

Specifications

Marque	Bitzer
Le type	4N.2
Réfrigérant	Freon
kW at 0°C/+40°C	47,9
kW at -5°C/+40°C	39,9
kW at -10°C/+40°C	32,9
kW at -20°C/+40°C	21,7
kW at -30°C/+40°C	13,4
kW at -40°C/+40°C	7,5
kW at -45°C/+40°C	5,2
Démarrage à vide	✓
Contrôle de capacité	✓
Système de niveau d'huile	✓
Electrovanne	✓
m ³ / h	27,0 m ³ /h at 700 RPM & 67,7 m ³ /h at 1750 RPM
Weight	170
Tailles	1060x550x500 mm (LxWxH)
Stock	1



Description

Used Bitzer 4N.2

Used Bitzer 4N.2 open-type reciprocating compressor on Freon. Complete with a Leroy-Somer P160L-T electric motor - 50 Hz - 15 kW - 1435 RPM, capacity control, unloaded start and an oil level regulator. The compressor has a displacement of 27 m³/h at 700 RPM & 67,7 m³/h at 1750 RPM.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also perform a new paint job and arrange the logistics.



