

# Bock HGX22e/160-4 S Compressor package

## Specifications

Marque	Bock
Le type	HGX22e/160-4 S Compressor package
Réfrigérant	Freon
kW at 0°C/+40°C	11,20
kW at -5°C/+40°C	9,17
kW at -10°C/+40°C	7,54
kW at -20°C/+40°C	4,81
kW at -30°C/+40°C	2,75
kW at -40°C/+40°C	1,33
Sur le châssis en acier	✓
Interrupteurs de sécurité de pression	✓
Réservoir de liquide	✓
Réservoir de liquide ltr.	19
Séparateur d'huile	✓
Liquid déshydrateur ligne	✓
Voyant	✓
Panneau de configuration	✓
m3 / h	13
Package / Rack	✓
Tailles	900x670x1400 mm
Stock	1



## Description

### Used Bock HGX22e/160-4 S Compressor package

Used Bock HGX22e/160-4 S compressor unit. Complete with liquid receiver, oil separator, control panel, pressure safety switches and liquid line filter.

\*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

\*Optional we can also arrange the logistics.







# Your partner for used commercial and industrial refrigeration equipment

R404A/R507		Performance data												50 Hz
Type	Cond. temp. °C	Cooling capacity Q <sub>0</sub> [kW]												Power consumption P <sub>e</sub> [kW]
		Evaporating temperature °C												
		7.5	5	0	-5	-10	-15	-20	-25	-30	-35	-40	-45	
HGX12P/60-4 1)	30 Q	6525	5989	4990	4108	3326	2667	2094	1610	1207	878	616	414	
	P	1,20	1,22	1,23	1,20	1,15	1,08	1,00	0,91	0,81	0,71	0,62	0,53	
	Q	5537	5060	4191	3428	2764	2193	1706	1297	959	684	465	296	
HGX12P/60-4	40 Q	4535	4128	3390	2748	2195	1723	1324	993	722	503	329		
	P	1,72	1,69	1,60	1,49	1,37	1,24	1,10	0,96	0,83	0,70	0,59		
	Q	2327	1851	1442	1097	809	573							
HGX12P/75-4 1)	30 Q	8160	7498	6284	5227	4288	3469	2764	2164	1661	1246	911	648	
	P	1,52	1,54	1,55	1,50	1,45	1,37	1,26	1,15	1,03	0,91	0,79	0,68	
	Q	6934	6357	5304	4419	3606	2902	2299	1789	1364	1015	734	513	
HGX12P/75-4 5 1)	40 Q	5729	5238	4345	3632	2945	2355	1855	1435	1087	804	577		
	P	2,21	2,17	2,05	1,92	1,78	1,62	1,45	1,29	1,12	0,96	0,82		
	Q	2888	2296	1789	1361	1004	711							
HGX12P/90-4 1)	30 Q	9738	8948	7500	6085	5000	4052	3231	2529	1937	1446	1047	730	
	P	1,85	1,86	1,86	1,78	1,69	1,58	1,46	1,32	1,18	1,03	0,89	0,75	
	Q	8288	7600	6344	5145	4202	3381	2676	2075	1571	1155	817	549	
HGX12P/90-4 5 1)	40 Q	6863	6276	5212	4219	3418	2727	2137	1640	1226	886	611		
	P	2,66	2,60	2,46	2,25	2,06	1,85	1,65	1,44	1,24	1,04	0,86		
	Q	3407	2688	2089	1574	1146	796							
HGX12P/110-4 1)	30 Q	11247	10345	8691	7218	5966	4868	3914	3094	2397	1814	1334	946	
	P	2,17	2,18	2,16	2,15	2,05	1,92	1,76	1,59	1,41	1,23	1,05	0,88	
	Q	9581	8796	7361	6125	5039	4091	3270	2567	1972	1473	1062	728	
HGX12P/110-4 5 1)	40 Q	7877	7211	6000	5010	4095	3301	2619	2039	1549	1141	803		
	P	3,12	3,05	2,89	2,74	2,50	2,25	1,99	1,73	1,49	1,26	1,05		
	Q	4092	3265	2558	1960	1461	1051							
HGX22e/125-4	30 Q	13400	12400	10500	8790	7250	5870	4650	3590	2680	1920	1320	857	
	P	2,19	2,23	2,26	2,24	2,16	2,03	1,88	1,69	1,49	1,28	1,07	0,878	
	Q	11660	10700	8970	7460	6090	4880	3820	2900	2120	1490	992	640	
HGX22e/125-4 5 1)	40 Q	9520	8860	7390	6080	4910	3880	2990	2230	1610	1110	749		
	P	3,26	3,19	3,03	2,84	2,60	2,34	2,07	1,80	1,53	1,27	1,03		
	Q	4728	3791	2981	2291	1715	1247							
HGX22P/125-4	30 Q	16900	15600	13200	10900	8980	7200	5800	4560	3450	2510	1750	1170	
	P	2,71	2,75	2,78	2,73	2,62	2,47	2,29	2,07	1,84	1,59	1,34	1,08	
	Q	14500	13400	11200	9170	7540	6090	4810	3700	2750	1960	1330	851	
HGX22e/160-4 5 1)	40 Q	12100	11100	9150	7480	6090	4860	3790	2860	2090	1460	971		
	P	4,02	3,94	3,79	3,51	3,22	2,90	2,58	2,25	1,92	1,60	1,30		
	Q	9480	8600	7000	5690	4590	3620	2810	2090	1520	1080	740		