

Bitzer 6F-40.2Y-40P (x2) / 66F-80.2Y-40P

Specifications

| | |
|------------------------------|-----------------------------------|
| Merk | Bitzer |
| Type | 6F-40.2Y-40P (x2) / 66F-80.2Y-40P |
| Koudemiddel | Freon |
| kW at -10°C/+40°C | 166,2 |
| kW at -20°C/+40°C | 108,5 |
| kW at -30°C/+40°C | 65,9 |
| kW at -40°C/+40°C | 35,1 |
| kW at -45°C/+40°C | 23,4 |
| Capaciteits Controle | ✓ |
| Op stalen frame | ✓ |
| Druk veiligheids schakelaars | ✓ |
| Manometers | ✓ |
| Vloeistof tank | ✓ |
| Suction accumulator | ✓ |
| Olie afscheider | ✓ |
| Kijk glas | ✓ |
| m3 / h | 303,2 |
| Opmerkingen | Y.o.b. 2008 |
| Afmetingen | 2300x1100x1580 mm (LxWxH) |
| Stock | 2 |



Description

Used Bitzer 6F-40.2Y-40P (x2) / 66F-80.2Y-40P

Gebruikte Bitzer 6F-80.2Y-40P (x2) compressor unit op Freon. Compleet met Bitzer 66F-80.2Y-40P semi-hermetische tandemcompressor, vloeistofreservoir, zuigaccumulator, Temprite 927 olieafscheider, zuigaccumulator, druk- en veiligheidsschakelaars/meters en een schakelkast met 1 Eliwell EWCM 9100 en 2 Eliwell ID974LK displays .





