

Bitzer 4DC-5.2Y-40S Condensing unit

Specifications

Merk	Bitzer
Type	4DC-5.2Y-40S Condensing unit
Koudemiddel	Freon
kW at -5°C/+40°C	17,7
kW at -10°C/+40°C	14,5
kW at -20°C/+40°C	9,5
kW at -30°C/+40°C	5,7
kW at -40°C/+40°C	3,0
kW at -45°C/+40°C	2,0
Op stalen frame	✓
Druk veiligheids schakelaars	✓
Vloeistof tank	✓
Vloeistof tank ltr.	13
Kijk glas	✓
m3 / h	26,9 - 32,4
Opmerkingen	Y.o.b. 2012
Condensing Unit	✓
Afmetingen	1000x750x950 mm (LxWxH)
Stock	1



Description

Used Bitzer 4DC-5.2Y-40S Condensing unit

Gebruikte condensing unit met een bitzer 4DC-5.2Y-40S semi-hermetische zuigercompressor op Freon gebouwd in 2012. Compleet met een condensor met een Ziehl-Abegg FB045-4EK.4L-V4P ventilator - 50/60 Hz - 0,48/ 0,73 kW - 1340/1530 RPM - diameter 450 mm, Bitzer FS126 vloeistofvat met een inhoud van 13 liter en druk- en veiligheidsschakelaars. De compressor heeft een slagvolume tussen 26,9 en 32,4 m³/h.





