

Bitzer VSK3161-15Y-40S

Specifications

Merk	Bitzer
Type	VSK3161-15Y-40S
Koudemiddel	Freon
kW at +10°C/+40°C	36,3
kW at 0°C/+40°C	24,3
kW at -5°C/+40°C	19,5
kW at -10°C/+40°C	15,2
Onbelaste aanloop	✓
Capaciteits Controle	✓
Vloeistof tank	✓
Vloeistof tank ltr.	30
Olie level systeem AC&R	✓
m ³ / h	46 / 56
Opmerkingen	Y.o.b. 2013
Opmerkingen	*Capacities based on the use of Freon type: R134A
Afmetingen	1050x450x760 mm (LxWxH)
Stock	1



Description

Used Bitzer VSK3161-15Y-40S

Gebruikte Bitzer VSK3161-15Y-40S hermetische compacte schroefcompressor op Freon. Compleet met een Bitzer F302H vloeistofvat met een inhoud van 30 liter en een Emerson OM3-CCD elektrische oliepeilregelaar. De compressor heeft een cilinderinhoud van 46 m³/h bij 2900 RPM en 56 m³/h bij 3500 RPM.

Houd er rekening mee dat de onderstaande capaciteiten betrekking hebben op het Freon-type: R134A.



		Typ VSK3161-15Y-40S		S.Nr. 1085000360	
BITZER KÜHLMASCHINENBAU GMBH		Made in E.C.			
Nennspannung	Frequ.	Max. Betr. strom	Anlaufstrom	Fördervol.	Drehzahl
V(Δ) 3Ph~	V Y 3Ph~	Hz	A(Δ) A (Y)	A(Δ) A (Y)	m³/h min⁻¹
230	380-415	50	39 22	213 125	46 2900
275	440-480	60	39 22	213 125	56 3500
Volumen	V	18 L	Max. Betriebsdruck ND	PS	19 bar
Max.Betr.temp.	TS	120 °C	Max. Betriebsdruck HD	PS	25 bar
Herstelldatum		10/2013	Prüfdruck	PT	36 bar
		IP 66		CE 0036	

