

# Carrier 30 RQP 240

## Specifications

Merk	Carrier
Type	30 RQP 240
Product type	Heat pump
Capaciteit kW	272,0
Capaciteit Tons	77,3
Koudemiddel	Freon
Koudemiddel Type	R410A
Pump	✓
Hydronic Module	✓
Gewicht in kg.	2377
Afmetingen	3600x2250x2450 mm (LxWxH)
Compressor(s) type & model	Performer SH295A4ACE (x2) & SH240A4ACE (x2)
Display	Carrier Touch Pilot
Number of fans	5
Opmerkingen	Y.o.b. 2017
Stock	2



## Description

### Used Carrier 30 RQP 240


Gebruikte Carrier 30 RQP 240 warmtepomp op R410A bouwjaar 2017. Compleet met 2 Performer SH295A4ACE & 2 Performer SH240A4ACE scroll compressoren, condensator met 5 ventilatoren die een luchtverplaatsing hebben van 81.248 m<sup>3</sup>/h, platenwisselaar als verdamper met een watervolume van 27 liter, 2 vloeistofleiding filterdrogers, expansievat, Lowara waterpomp, 2 Danfoss VLT FC-102P4K0T4E55H frequentieomvormer en een Carrier Touch Pilot.



1- SERIAL-NUMBER NUMERO DI SERIE	M2017009526	CE 0062	
2- MODEL MODELLO	30RQP-240-0017-PE-		
47- DESCRIPTION DESCRIZIONE			
3- VARIANT VERSIONE	30RQM/RQP		
4- YEAR OF MANUFACTURE AND TEST DATE ANNO E DATA DI COSTRUZIONE	31/08/2017		
48- HERMETICALLY SEALED EQUIPMENT APPARECCHIATURE SIGILLATE ERMETICAMENTE	N		
49- CONTAINS FLUORIMATED GREENHOUSE GASES CONTIENE GAS FLUORURATI EFFETTO SERRA	Y		
25- FLUID DURING TRANSPORT LIQUIDI DURANTE IL TRASPORTO	R-410A	62.00 kg	
5- REFRIGERANT REFRIGERANTE	R-410A	6- PED GROUP ? GRUPPO PED	GWP 2088
50- CIRCUIT CIRCUITO	A / B / C		
7- FACTORY CHARGE CARICO FABBRICA	27.00 / 35.00	/*	kg
51- CHARGE ADDED ON SITE CARICO AGGIUNTO IN SEDE			kg
52- TOTAL CHARGE CARICO TOTALE	27.00 / 35.00	/*	kg
	56.38 / 73.08	/*	t. eq. CO2
9- INERTING MEDIUM CARICA DI TENUTA	23- NITROGEN		
10- ALLOWABLE PRESSURE MIN/MAX MIN/MAX PRESSIONE AMMISSIBILE	(PS) 21- HIGH PRESSURE ALTA PRESSIONE	22- LOW PRESSURE BASSA PRESSIONE	
	(PS) -1.0 / 44.9 bar	-1.0 / 31.1 bar	
	-99.0 / 4490.0 kPa	-99.0 / 3110.0 kPa	
11- ALLOWABLE TEMPERATURE MIN/MAX MIN/MAX TEMPERATURA AMMISSIBILE	(TS) -20.0 / 68.0 °C	-20.0 / 52.0 °C	
12- PRESSURE SAFETY SWITCH SETTING 1/2 TARATURA PRESSOSTATI DI SICUREZZA 1/2	44.2 /*	bar /*	bar
13- RELIEF VALVE SETTING PRESSIONE DI INTERVENTO VALVOLA DI SICUREZZA	/*	bar	bar
24- RUPTURE DISKS SETTING PRESSIONE DI INTERVENTO DEI DISCHI DI ROTTURA	/*	bar	bar
14- UNIT LEAK TEST PRESSURE PRESSIONE DI PROVA		17.0 bar	
15- VOLTAGE TENSIONE	400 V +10 % -10 %	16- PHASES 3 FASE	17- FREQUENCY ~ 50 Hz FREQUENZA
18- MAXIMUM AMPS MAX CORRENTE	203.00 /*	A	44- IP S4 IP
19- MAX POWER INPUT POTENZA ASSORBITA	125.00 /*	kW	
20- NET WEIGHT PESO NETTO	2377 kg	+5 % -5 %	

**Carrier** MANUFACTURED IN FRANCE BY  
CARRIER SCS - 01120 MONTLUEL - FRANCE  
AN AFFILIATED COMPANY OF CARRIER CORPORATION  
FARMINGTON CT, USA

United Technologies



PLS\_Tr1ckL\_V4r1

