

Bitzer 4G-30.2Y-40P

Specifications

| | |
|-------------------------|-----------------------------|
| Merk | Bitzer |
| Type | 4G-30.2Y-40P |
| Koudemiddel | Freon |
| kW at 0°C/+40°C | 68,6 |
| kW at -5°C/+40°C | 57,0 |
| kW at -10°C/+40°C | 47,0 |
| kW at -20°C/+40°C | 30,7 |
| kW at -30°C/+40°C | 18,6 |
| kW at -40°C/+40°C | 9,8 |
| Onbelaste aanloop | ✓ |
| Capaciteits Controle | ✓ |
| Manometers | ✓ |
| Condensatiedruk | ✓ |
| switches | |
| Olie afscheider | ✓ |
| Olie level systeem AC&R | ✓ |
| Magneet Afsluiter | ✓ |
| m ³ / h | 84,5 - 101,98 |
| Gewicht in kg. | 206 |
| Afmetingen | 1550x640x1000 mm (LxWxH) |
| Stock | 1 |



Description

Used Bitzer 4G-30.2Y-40P

Gebruikte Bitzer 4G-30.2Y-40P semi-hermetische zuigercompressor op Freon. De compressor heeft een cilinderinhoud van 84,5 m³/h bij 1450 RPM en 101,98 m³/h bij 1750 RPM.



