

Mycom FM160L-M/A

Specifications

Merk	Mycom
Type	FM160L-M/A
Koudemiddel	NH 3 (ammonia)
kW at 0°C/+40°C	575,9
kW at -5°C/+40°C	474,8
kW at -10°C/+40°C	387,5
kW at -20°C/+40°C	248,7
kW at -30°C/+40°C	149,8
kW at -40°C/+40°C	81,6
kW at -45°C/+40°C	56,7
Elektromotor Specs	50 Hz - 132 kW - 2955 RPM
Onbelaste aanloop	✓
Capaciteits Controle	✓
Manometers	✓
Olie afscheider	✓
Magneet Afsluiter	✓
Schakelkast	✓
Package / Rack	✓
Afmetingen	3600x1200x2400 mm (LxWxH)
Stock	1



Description

Used Mycom FM160L-M/A

Gebruikte Mycom FM160L-M/A schroefcompressor unit op R717 (NH3). Compleet met een Leroy Somer elektromotor - 50 Hz - 132 kW - 2955 RPM, Mycom HS 5023 olieafscheider met een inhoud van 465 liter, OWDA GF 220+1400/S oliekoeler, Mycom MAA 3066 oliefilter, manometers, Grundfos UPS 40-180/2F waterpomp en een schakelkast met een Mycom MYPRO-CP3 display.





