

Bitzer IIIY Condensing Unit

Specifications

Merk	Bitzer
Type	IIIY Condensing Unit
Koudemiddel	Freon
kW at +10°C/+40°C	3,5*
kW at 0°C/+40°C	2,3*
kW at -5°C/+40°C	1,3*
kW at -10°C/+40°C	0,6*
kW at -20°C/+40°C	0,4*
Vloeistof tank	✓
Vloeistof tank ltr.	5,6 l
Filter droger	✓
Kijk glas	✓
m ³ / h	4,0-9,4 m ³ /h
Opmerkingen	Y.o.b. 2006
Opmerkingen	* Freon type R404A and motor pulley 130mm
Condensing Unit	✓
Afmetingen	850x600x620 mm (LxWxH)
Stock	1



Description

Used Bitzer IIIY Condensing Unit

Gebruikte Bitzer L40/IIIY condensorunit op Freon. Compleet met een Bitzer IIIY semi-hermetische zuigercompressor, condensor met 1 ventilator, Bitzer FS 53 vloeistofontvanger met een inhoud van 5,6 liter, rotor nl UD 0701/1048670-034-9 elektromotor - 50/60 Hz - 6, 4/3,45 kW - 1410/1710 tpm, Danfoss DML 083 vloeistofleiding filterdroger en een kijkglas. De compressor heeft een cilinderinhoud tussen 4,0 m³/h en 9,4 m³/h.







