

Vilter VSM601CIHSTDSDA

Specifications

Merk	Vilter
Type	VSM601CIHSTDSDA
Koudemiddel	NH 3 (ammonia)
kW at -10°C/+40°C	805,0* (-6,67°C/+35°C)
Op stalen frame	✓
Druk veiligheids schakelaars	✓
Manometers	✓
Olie afscheider	✓
Filter droger	✓
Kijk glas	✓
Magneet Afsluiter	✓
m3 / h	1.035
Opmerkingen	*Tons and BHP based on + 20°F and 95°F; 10°F liquid subcooling, saturated suction, 0°F superheat.
Condensing Unit	✓
Afmetingen	3460x1750x2840 mm (LxWxH)
Stock	3



Description

Used Vilter VSM601CIHSTDSDA

Gebruikte Vilter VSM601CIHSTDSDA enkelschroefcompressorunit op NH3 (ammoniak). Compleet met Leroy Somer LSRPM250SE-T - 190 kW - 3600 tpm, C.T.N. OSP0700192PERE olieafscheider met een inhoud van 825 liters, manometers/schakelaar, Viking oliepomp met Lambert Moteurs elektromotor - 50/60 Hz - 2,2/2,64 kW - 1415/1700 tpm en een SART von Rohr PA 35 B6 2G PO pneumatische actuator. De compressor heeft een cilinderinhoud van 1.035 m³/u.









