

Goedhart DVS 61454

Specifications

Merk	Goedhart
Type	DVS 61454
Capaciteit kW	9,3
Koudemiddel	Freon
Aantal Ventilatoren	1
Lamel afstand in mm	4
Ontdooiing	None
Dubbel blazend	✓
m ³ /h	4239
Afmetingen	1040x1470x520 mm
Opmerkingen	Y.o.b. 1997
Remarks	Surface 78 m ²
Volume	12,0 dm ³
Gewicht	99 kg
Stock	10



Description

Used Goedhart DVS 61454

Used Goedhart DVS 61454 double discharge evaporator with a Woods fan. Min. workingtemp. -5°C max. 43°C. *All components of this used evaporator will be tested on good working, leak free condition (electro engines), coils, bearings) Choosing HOSBV means buying with warranty. We perform an industrial cleaning and rust spots will be covered. Also, we can arrange your shipment.



DVS 4mm Technical data

Type DVS	3460V-50H-epole (1500 min./room.)				3480V-50H-epole (1500 min./room.)				Dimensions						Connections								
	1500 min./room.		1500 min./room.		1500 min./room.		1500 min./room.		L	B	H	E1	E2	E3	E4	In	out						
	Power kW	DT K (°C)	Air volume m ³ /h	DT K (°C)	Air volume m ³ /h	Power kW	DT K (°C)	Air volume m ³ /h	DT K (°C)	Air volume m ³ /h	Surface m ²	Intensity kg/dm ³	Weight kg	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
4.1.30.4	0.5	4.9	3582	52	11	1892	41	39	6	100	1056	1180	420	656				15	15	4619	2419		
4.1.35.4	0.7	6.6	2837	52	11	1790	41	58	10	120	1056	1280	420	656				22	12	4619	2419		
4.1.40.4	0.9	7.8	4610	56	11	2901	47	52	8	116	1056	1230	520	656				22	12	4619	2419		
4.1.45.4	1.2	8.8	4239	56	11	2623	50	78	12	140	1056	1430	520	656				22	12	4619	2419		
4.1.50.4	1.6	16.2	6246	63	10.4	4594	59	78	12	147	1396	1280	520	956				22	12	4619	2419		
4.1.55.4	1.9	14.0	6527	63	10.5	4215	50	117	16	162	1396	1430	520	956				28	16	4619	2419		
4.1.56.4	1.8	16.4	9904	63	10.7	6294	53	106	16	182	1496	1340	620	1056				28	16	4619	2419		
4.1.58.4	2.1	20.3	9381	63	10.7	5842	53	162	24	226	1496	1540	620	1056				35	16	4619	2419		
4.1.61.4	2.0	19.0	12071	63	10.8	8620	58	190	26	203	1496	1610	720	1056				35	16	4619	2419		
4.1.61.4	3.0	24.4	11387	63	10.7	8283	58	195	30	254	1496	1610	720	1056				35	16	4619	2419		

