

Bitzer 4T.2 tank aggregate

Specifications

Merk	Bitzer
Type	4T.2 tank aggregate
Koudemiddel	Freon
kW at 0°C/+40°C	47.86
kW at -10°C/+40°C	32.9
kW at -20°C/+40°C	21.67
kW at -30°C/+40°C	13.39
kW at -40°C/+40°C	7.55
Elektromotor Specs	N/A
Opmerkingen	We would like to know which refrigerant is in your system
Stock	1



Description

Used Bitzer 4T.2 tank aggregate

Gebruikt tankaggregaat met een Bitzer 4-T semi-hermetische zuigercompressor en elektromotor. "*
 Waarom kiezen voor HOSBV? We waren niet alleen de grootste specialist in gebruikte koeling in Europa, maar we leveren ook alle apparatuur, inclusief een uitgebreide test, garantie en industriële reiniging. Optioneel kunnen we verzend- en exportdocumenten regelen."



t _c	t ₀	COP [-]				COPIER			
		0°C	-10°C	-20°C	-30°C	-40°C	-50°C	-60°C	-70°C
30°C	Q [W]	55782	38512	25606	16127	9342	--	--	--
	Q' [W]	55782	38512	25606	16127	9342	--	--	--
	P [kW]	11,18	10,28	8,90	7,25	5,55	--	--	--
	Qc [W]	60561	48794	34505	23376	14882	--	--	--
	COP [-]	4,99	3,75	2,88	2,22	1,68	--	--	--
	COP' [-]	4,99	3,75	2,88	2,22	1,68	--	--	--
	m [kg/h]	1418	958	627	391	225	--	--	--
n [1/min]	1450	1450	1450	1450	1450	--	--	--	
40°C	Q [W]	47861	32907	21674	13395	7456	--	--	--
	Q' [W]	47861	32907	21674	13395	7456	--	--	--
	P [kW]	12,70	11,36	9,64	7,75	5,91	--	--	--
	Qc [W]	60559	44271	31317	21148	13368	--	--	--
	COP [-]	3,77	2,90	2,25	1,73	1,26	--	--	--
	COP' [-]	3,77	2,90	2,25	1,73	1,26	--	--	--
	m [kg/h]	1373	921	596	364	201	--	--	--
n [1/min]	1450	1450	1450	1450	1450	--	--	--	
50°C	Q [W]	39849	27292	17777	10715	5614	--	--	--
	Q' [W]	39849	27292	17777	10715	5614	--	--	--
	P [kW]	14,36	12,62	10,60	8,51	6,56	--	--	--
	Qc [W]	47856	35013	25178	16553	11171	--	--	--
	COP [-]	2,73	2,17	1,62	1,23	0,86	--	--	--
	COP' [-]	2,73	2,17	1,62	1,23	0,86	--	--	--
	m [kg/h]	1150	750	500	300	170	--	--	--