

# Trane CSHA 150K

## Specifications

Merk	Trane
Type	CSHA 150K
Koudemiddel	Freon
kW at +10°C/+40°C	57,0
kW at 0°C/+40°C	39,0
kW at -5°C/+40°C	31,7
kW at -10°C/+40°C	25,4
kW at -20°C/+40°C	15,5
m <sup>3</sup> / h	43,5
Gewicht in kg.	100
Afmetingen	350x400x700 mm
Stock	2



## Description

### Used Trane CSHA 150K

Gebruikte Trane CSHA 150K scrollcompressor, hetzelfde als Performer SM185S4Q. Bouwjaar 2002.



### R-22, R-407C

#### Product Selection

Nominal Torque	Wph/Rz	Competitor Part Nos. <sup>1</sup>	R-22		R-407C		Net Weight (lbs.)	Connection Size/Type (Suction x Discharge)	Solder Sleeve Adapter Part for Solderless Connectors
			Danfoss Model No.	Danfoss Code No.	Danfoss Model No.	Danfoss Code No.			
7½	200-230/3/60		ZR94KC-TFS	SM09053V*	SM090-3VI	SZ09053VC	SZ090-3VI	1 1/4" x 1/4" Brazed	7765005
	460/3/60		ZR94KC-TFD	SM09054V*	SM090-4VI	SZ09054VC	SZ090-4VI		
9.3	200-230/3/60	CSHA-093R-0"00 or 0A CSHS-093R-0"00 or 0A	ZR108KC-TFS ZR11M3-TWC	SM11553Q*	SM115-3QAI	SZ11553QC	SZ115-3QAI	1 1/4" x 1/4" Brazed	12020405
	460/3/60		ZR108KC-TFD ZR11M3-TWD	SM11554Q*	SM115-4QAI	SZ11554QC	SZ115-4QAI		
10	200-230/3/60	CSHA-100R-0"00 or 0A CSHS-100R-0"00 or 0A	ZR125KC-TFS ZR12M3-TWC	SM12553Q*	SM125-3QAI	SZ12553QC	SZ125-3QAI	1 1/4" x 1/4" Brazed	12020405
	460/3/60		ZR125KC-TFD ZR12M3-TWD	SM12554Q*	SM125-4QAI	SZ12554QC	SZ125-4QAI		
12½	200-230/3/60	CSHA-125R-0"00 or 0A	ZR16M3-TWC	SM16073C*	SM160-3CBI	SZ16073CC	SZ160-3CBI	1 1/4" x 1/4" Brazed	7765008
	460/3/60		ZR16M3-TWD	SM16074C*	SM160-4CBI	SZ16074CC	SZ160-4CBI		
14	200-230/3/60	CSHA-140R-0"00 or 0A CSHS-140R-0"00 or 0A	ZR175KC-TFS ZR17M3-TWC	SM17553Q*	SM175-3QAI	SZ17553QC	SZ175-3QAI	1 1/4" x 1/4" Brazed	7765008
	460/3/60		ZR175KC-TFD ZR17M3-TWD	SM17554Q*	SM175-4QAI	SZ17554QC	SZ175-4QAI		
15	200-230/3/60	CSHA-150R-0"00 or 0A CSHS-150R-0"00 or 0A	ZR190KC-TFS ZR19M3-TWC	SM18553Q*	SM185-3QAI	SZ18553QC	SZ185-3QAI	1 1/4" x 1/4" Brazed	7765008
	460/3/60		ZR190KC-TFD ZR19M3-TWD	SM18554Q*	SM185-4QAI	SZ18554QC	SZ185-4QAI		