

Prestcold P3D150X (x1) / PL40X (2x) / P3D100X (x1)

Specifications

Marka	Prestcold
Typ	P3D150X (x1) / PL40X (2x) / P3D100X (x1)
Czynnik chłodzący	Freon
kW at 0°C/+40°C	105,0
kW at -5°C/+40°C	87,3
kW at -10°C/+40°C	71,7
kW at -20°C/+40°C	46,7
kW at -30°C/+40°C	28,5
kW at -40°C/+40°C	15,3
Podstawa na stalowej ramie	✓
Separator oleju	✓
Poziom oleju w systemie	✓
Osuszający filter lini cieczy	✓
Okno widokowe	✓
Uwagi	Y.O.B. 2002
Package / Rack	✓
Rozmiary	2800x1240x2250 mm (LxWxH)
Stock	1



Description

Used Prestcold P3D150X (x1) / PL40X (2x) / P3D100X (x1)

Used Prestcold soundproof compressor unit. Complete with Prestcold P3D150x (1x), PL40x (2x), p3d100x (1x) compressors, Oil separator, Oil level system AC&R, Liquid line filter drier, Sight Glass and Danfoss Adap-Kool AKA 245 084B2268.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment solely if it has passed our extensive test. Warranty and industrial cleaning are included in your purchase. *If requested we are happy to arrange your shipment.





