

Bitzer 4N.2 Condensing unit

Specifications

Marka	Bitzer
Typ	4N.2 Condensing unit
Czynnik chłodzący	Freon
kW at 0°C/+40°C	47,9
kW at -5°C/+40°C	39,9
kW at -10°C/+40°C	32,9
kW at -20°C/+40°C	21,7
kW at -30°C/+40°C	13,4
kW at -40°C/+40°C	7,5
kW at -45°C/+40°C	5,2
Silnik elektryczny Specs	50 Hz - 11 kW - 1440 RPM
Podstawa na stalowej ramie	✓
Ciśnieniowe przełączniki bezpieczeństwa	✓
Obiornik cieczy	✓
Obiornik cieczy ltr.	36
Osuszający filter linii cieczy	✓
Okno widokowe	✓
m ³ / h	67,7
Condensing Unit	✓
Rozmiary	2150x750x1870 mm (LxWxH)
Stock	1



Description

Used Bitzer 4N.2 Condensing unit

Used Bitzer 4N.2 condensing unit on Freon. Complete with 1 Bitzer 4N.2 open-type reciprocating compressor, condenser with 4 Ziehl-Abegg fans - 50 Hz - 0,15 kW - 1500 RPM and a diameter of 400 mm, VEM KPER 160 M 4 elektromotor - 50 Hz - 11 kW - 1440 RPM, Friga-Bohn RSV 36 liquid receiver, liquid line filter drier and a control box. *Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we solely deliver our orders after performing an extensive test and an industrial cleaning. If requested we are happy to arrange your logistics.





