

Sabroe SMC 108 L

Specifications

Marka	Sabroe
Typ	SMC 108 L
Czynnik chłodzący	NH 3 (ammonia)
kW at +10°C/+40°C	722,4
kW at 0°C/+40°C	477,8
kW at -5°C/+40°C	380,2
kW at -10°C/+40°C	297,1
Rozładunek	✓
Kontrolka wydajności	✓
Podstawa na stalowej ramie	✓
Ciśnieniowe przełączniki bezpieczeństwa	✓
Wskaźniki ciśnienia	✓
Separator oleju	✓
Okno widokowe	✓
Zawór elektromagnetyczny	✓
m ³ / h	550
Rozmiary	2200x1100x1200 mm (LxWxH)
Stock	1



Description

Used Sabroe SMC 108 L

Inspected and ready to run Sabroe SMC 108 L reciprocating compressor on NH3 (R717). Complete with a ALSTHOM APU 280 S electric motor - 50 Hz - 110 kW - 1460 RPM, Sabroe OVUR 3206 D oil separator and pressure and safety switches/gauges. The compressor has a displacement of 550 m³/h. The compressor will get a freshly spray paint.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning. *Optionally we can also perform a new paint job and arrange the logistics.





