

Bitzer OSNA 5361-K

Specifications

Marka	Bitzer
Typ	OSNA 5361-K
Czynnik chłodzący	NH 3 (ammonia)
kW at -10°C/+40°C	87,4
kW at -20°C/+40°C	58,4
kW at -30°C/+40°C	36,4
Silnik elektryczny Specs	50/60 Hz - 30/34 kW - 2935/3540 RPM
Podstawa na stalowej ramie	✓
Ciśnieniowe przełączniki bezpieczeństwa	✓
Wskaźniki ciśnienia	✓
Separator oleju	✓
m ³ / h	59-183
Uwagi	Y.o.b. 2001
Uwagi	Please note: we will only offer this as complete blastfreezing solution with capacity matching condensor and evaporators.
Uwagi	*Capacity calculated with economizer
Rozmiary	1650x1150x1600 mm (LxWxH)
Stock	1



Description

Used Bitzer OSNA 5361-K

Used Bitzer OSNA 5361-K open screw compressor on NH₃. Complete with 1 Leroy Somer PLS180M-T electric motor - 50/60 Hz - 30/34 kW - 2935/3540 RPM, Bitzer OA 1854A oil separator with a volume of 40 liter, Bitzer OAS 322 secondary oil separator, braced heat exchanger, pressure and safety switches/gauges, control box and LAE MT 11 digital thermostat. The compressor has a displacement between 59 and 183 m³/h. *Capacity calculated with economizer.

Please note: we will only offer this as complete blastfreezing solution with capacity matching condensor and evaporators.


*Why choose for HOSBV? Were not only



the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also perform a new paint job and arrange the logistics.




 Typ OSNA 5361-K
 S.Nr. 16050339
BITZER KÜHLMASCHINENBAU GMBH
 Made in E.C.

Fördervolumen m³/h	Drehzahl min⁻¹
59-183	1450-4500

ND/HD max. 19 / 28 bar
378 027-01

