

Howden MK4AS/XRV204145MVI

Specifications

Marka	Howden
Typ	MK4AS/XRV204145MVI
Czynnik chłodzący	NH 3 (ammonia)
kW at 0°C/+40°C	806,1
kW at -5°C/+40°C	643,7
kW at -10°C/+40°C	505,6
kW at -20°C/+40°C	295,4
kW at -30°C/+40°C	148,8
Silnik elektryczny Specs	50/60 Hz - 200/230 kW - 2975/3575 RPM
Podstawa na stalowej ramie	✓
Ciśnieniowe przełączniki bezpieczeństwa	✓
Przełączniki kondensacji ciśnienia	✓
Separator oleju	✓
m ³ / h	1070
Uwagi	*Capacity based on the following temperatures: (-10°C/+35°C)
Uwagi	**Capacity based on the following temperatures: (-35°C/+35°C)
Waga kg.	+3300 kg
Rozmiary	2930x1250x2250 mm (LxWxH)



Stock

2

Description

Used Howden MK4AS/XRV204145MVI

Used Howden MK4AS/XRV204145MVI open-type screw compressor set on R717 (NH3). Complete with a Schorch KN7315M-AB01B-401 electric motor - 50/60 Hz - 200/230 kW - 2975/3575 RPM, Samifi Babcock SHH 600 oil separator, HS-Cooler KS12-AEH-122 oil cooler, Samifi Babcock FI150 104 oil filter, pressure and safety switches and condensing pressure switch. The compressor has a displacement of 1070 m³/h.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning. *Optionally we can also perform a new paint job and arrange the logistics.







