

Bitzer 2U-5.2 Water cooled condensing unit

Specifications

Marka	Bitzer
Typ	2U-5.2 Water cooled condensing unit
Czynnik chłodzący	Freon
kW at 0°C/+40°C	15,2
kW at -5°C/+40°C	12,6
kW at -10°C/+40°C	10,3
kW at -20°C/+40°C	6,7
kW at -30°C/+40°C	4,1
Rozładunek	✓
Podstawa na stalowej ramie	✓
Ciśnieniowe przełączniki bezpieczeństwa	✓
Wskaźniki ciśnienia	✓
Obiornik cieczy	✓
Osuszający filter lini cieczy	✓
Okno widokowe	✓
Zawór elektromagnetyczny	✓
Panel kontrolny	✓
m ³ / h	18,6 m ³ /h
Condensing Unit	✓



(LxWxH)

Bitzer

1200x820x920 mm

Description

Used Bitzer 2U-5.2 Water cooled condensing unit

Used water cooled condensing unit on Freon. Complete with a Bitzer 2U-5.2 semi-hermetic reciprocating compressor, Bitzer K202 HB shell and tube condenser, liquid receiver, pressure and safety switches/gauges and a control cabinet. The compressor has a displacement of 18,6 m³/h.

*Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment solely if it has passed our extensive test. Warranty and industrial cleaning are included in your purchase.
*If requested we are happy to arrange your shipment.





