

# Bitzer IIIY Condensing Unit

## Specifications

Marka	Bitzer
Typ	IIIY Condensing Unit
Czynnik chłodzący	Freon
kW at +10°C/+40°C	3,5*
kW at 0°C/+40°C	2,3*
kW at -5°C/+40°C	1,3*
kW at -10°C/+40°C	0,6*
kW at -20°C/+40°C	0,4*
Obiornik cieczy	✓
Obiornik cieczy ltr.	5,6 l
Osuszający filter lini cieczy	✓
Okno widokowe	✓
m <sup>3</sup> / h	4,0-9,4 m <sup>3</sup> /h
Uwagi	Y.o.b. 2006
Uwagi	* Freon type R404A and motor pulley 130mm
Condensing Unit	✓
Rozmiary	850x600x620 mm (LxWxH)
Stock	1



## Description

### Used Bitzer IIIY Condensing Unit

Used Bitzer L40/IIIY condensing unit on Freon. Complete with a Bitzer IIIY semi-hermetic reciprocating compressor, condenser with 1 fan, Bitzer FS 53 liquid receiver with a volume of 5,6 liters, rotor nl UD 0701/1048670-034-9 electric motor - 50/60 Hz - 6,4/3,45 kW - 1410/1710 RPM, Danfoss DML 083 liquid line filter drier and a sight glasses. The compressor has a displacement between 4,0 m<sup>3</sup>/h and 9,4 m<sup>3</sup>/h.

\*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we solely deliver our orders after performing an extensive test and an industrial cleaning. If requested we are happy to arrange your logistics.







