

# Helpman HTC 091-124

## Specifications

|  |  |
|--|--|
| Marka                                  | Helpman  |
| Typ                                    | HTC 091-124  |
| Typ produktu                           | Drycooler  |
| Ogólna wydajność w kW                  | 295,6*   |
| Liczba wentylatorów                    | 2  |
| Prdkość obrotów wentylatora (obr/min)  | 850/610  |
| Czynnik chłodzący                      | Glycol   |
| Przepływ powietrza w m <sup>3</sup> /h | 57.400   |
| wentylatory o średnicy Ø 910 mm        |  |
| Powierzchnia (m <sup>2</sup> )         | 607 m <sup>2</sup>   |
| Objętość rurki                         | 51 dm <sup>3</sup>   |
| Rozmiary (LxWxH)                       | 4150x1250x1200 mm  |
| Waga                                   | 614 kg   |
| Uwagi                                  | *Capacity is based on a medium inlet temperature of 60°C and an outlet temperature of 40°C |
| Stock                                  | 1  |



## Description

### Used Helpman HTC 091-124

Used Helpman HTC 091-124 drycooler. Complete with 2 Ziehl-Abegg FE091-SDS.6N.6 fans - 50 Hz - 1,6/0,91 kW - 850/610 RPM - diameter 910 mm and a total airflow of 57.400 m<sup>3</sup>/h. The current condenser will be converted into a drycooler and the appropriate flanges will be installed. The drycooler has a capacity of 295,6kW with a medium inlet temperature of 60°C and an outlet temperature of 40°C. \*All components of this used condenser will be tested on adequate functionality, leak free condition (electro engines), condensing block, bearings. Choosing HOSBV means buying with warranty. We perform an industrial cleaning on demand, we can arrange your shipment.



