

Lu-Ve

Specifications

| | |
|--|--|
| Marka | Lu-Ve |
| Typ produktu | Drycooler |
| Ogólna wydajność w kW | 39,2* |
| Liczba wentylatorów | 4 |
| Prdkość obrotów wentylatora (obr/min) | 550 RPM |
| Czynnik chłodzący | Glycol |
| Przepływ powietrza w m ³ /h | 14.400 |
| wentylatory o średnicy Ø | 630 mm |
| Powierzchnia (m2) | 150,8 m ² |
| Rozmiary (LxWxH) | 4320x540x1100 mm |
| Uwagi | Y.o.b. 2011 |
| Remarks | *Capacity is based on a medium inlet temperature of 40°C and an outlet temperature of 35°C |
| Stock | 1 |



Description

Used Lu-Ve

Used Lu-ve drycooler. Complete with 4 EBM-Papst A8E630-AK05-05 fans - 50 Hz - 0,87A - 0,20 kW - 550 RPM - diameter 630 mm and a total airflow of 14.400 m³/h. The current condenser will be converted into a drycooler and the appropriate flanges will be installed. The drycooler has a capacity of 39,2kW with a medium inlet temperature of 40°C and an outlet temperature of 35°C.

*All components of this used condensor will be tested on good working, leak free condition (electro engines), condensing block, bearings. Choosing HOSBV means buying with warranty. We perform a industrial cleaning. Also, we can arrange your shipment.



