

# Bitzer LH84/4CC-6.2Y-40S Condensing Unit

## Specifications

Marka	Bitzer
Typ	LH84/4CC-6.2Y-40S Condensing Unit
Czynnik chłodzący	Freon
kW at -5°C/+40°C	21,1
kW at -10°C/+40°C	17,4
kW at -20°C/+40°C	11,4
kW at -30°C/+40°C	7,0
kW at -40°C/+40°C	3,8
Podstawa na stalowej ramie	✓
Ciśnieniowe przełączniki bezpieczeństwa	✓
Obiornik cieczy	✓
Obiornik cieczy ltr.	13 l
Separator oleju	✓
Osuszający filter lini cieczy	✓
Okno widokowe	✓
Panel kontrolny	✓
m <sup>3</sup> / h	50 Hz - 32,5 m <sup>3</sup> /h / 60 Hz - 39,2 m <sup>3</sup> /h
Uwagi	Y.o.b. 2006
Condensing Unit	✓



---

	(LxWxH)
Bitzerkiary	2000x700x950 mm

---

## Description

### Used Bitzer LH84/4CC-6.2Y-40S Condensing Unit

Used Bitzer LH84/4CC-6.2Y-40S condensing unit on Freon. Complete with 1 Bitzer 4CC-6.2Y-40S semi-hermetic reciprocating compressor, Bitzer FS126 liquid receiver with a volume 13 liters, pressure safety switches, Henry Technologies S-5585-CE oil separator, control panel and condenser with 1 Ziehl-Abegg FB045-4EK.4I.V4P fan - 50/60 Hz - 0,48/0,73 kW - 1340/1530 RPM - diameter 450 mm.

\*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning. \*Optionally we can also perform a new paint job and arrange the logistics.







