

# Bitzer 4H-15.2Y

## Specifications

Marka	Bitzer
Typ	4H-15.2Y
Czynnik chłodzący	Freon
kW at -5°C/+40°C	49,7
kW at -10°C/+40°C	41,1
kW at -20°C/+40°C	27,1
kW at -30°C/+40°C	9,2
kW at -40°C/+40°C	6,4
Kontrolka wydajności	✓
Podstawa na stalowej ramie	✓
Ciśnieniowe przełączniki bezpieczeństwa	✓
Obiornik cieczy	✓
Obiornik cieczy ltr.	45
Ssanie	✓
Separator oleju	✓
Osuszający filter lini cieczy	✓
Okno widokowe	✓
Zawór elektromagnetyczny	✓
m <sup>3</sup> / h	50 Hz - 73,6 m <sup>3</sup> /h / 60 Hz - 88,8 m <sup>3</sup> /h
Rozmiary	2330x750x1100 mm (LxW)
Stock	2



## Description

### Used Bitzer 4H-15.2Y

Used Bitzer 4H-15.2Y semi-hermetic reciprocating compressor on Freon. Complete with a suction accumulator, oil separator, liquid receiver with a volume of 45 liter, capacity control, liquid line filter drier, pressure and safety switches. The compressor has a displacement of 73,6 m<sup>3</sup>/h at 50 Hz & 88,8 m<sup>3</sup>/h at 60 Hz.

\*Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

\*Optional we can also perform a new paint job and arrange the logistics.





