

Bitzer 4T.2

Specifications

Marka	Bitzer
Typ	4T.2
Czynnik chłodzący	Freon
kW at +10°C/+40°C	46,5*
kW at 0°C/+40°C	40
kW at -5°C/+40°C	30
kW at -10°C/+40°C	24,8
kW at -20°C/+40°C	16,4
kW at -30°C/+40°C	10,2
kW at -40°C/+40°C	5,7
Silnik elektryczny Specs	11
Rozładunek	✓
Podstawa na stalowej ramie	✓
Ciśnieniowe przełączniki bezpieczeństwa	✓
Obiornik cieczy	✓
Osuszający filter lini cieczy	✓
Okno widokowe	✓
Panel kontrolny	✓
Uwagi	# // *Capacity based on +7,5°C/+40°C // Electromotor: 11 kW at 1445 RPM // Pulley EM: 240 mm / Compr: 220 mm



Uwagi	R404a - R22 or other freon types
Rozmiary	1400x750x1300 mm (LxWxH)
Stock	1

Description

Used Bitzer 4T.2

Used Bitzer 4T.2 freon compressor, complete with unloaded start, pressure safety switches, liquid receiver, liquid line filter drier, sight glass and control panel. This unit has a cooling capacity of 46,5 kW at +7,5°C/+40°C.

Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *Optional we can also perform a new paint job and arrange the logistics.



