

## Hermetic CAM 2/5

### Specifications

Marka	Hermetic
Rodzaj	CAM 2/5
Przepływ objętościowy Q 12,0 maks. (m <sup>3</sup> /h)	
Wysokość dostawy H maks. (M)	72,0
Moc maks. (kW)	4,3
Remarks	Y.o.b. 2009
Stock	1



### Description

#### Used Hermetic CAM 2/5

Hermetic CAM 2/5 liquid pump. 1-12 m<sup>3</sup>/h height 0-72 meters and 4,3 kW. Build in 2009.



LEDERLE Hermetic		
Equipmtennr.	4110010139/011-01	
Pumpen Typ	CAM 2/5	
Laufrad ø	130,0 mm	
Motor Typ	AGX3.0	
Q [m3/h]	Dichte [kg/m3]	H [m]
1,0 - 12,0	595,00 -	72,0 - 0,0
PN [bar]	P1 [kW]	f [Hz]
25,0	4,3	50,0 Hz
n [1/min]	cos phi	I [A]
2.720,0		7,1 A
Fl üssigkeitstemperatur max.	U [V]	
-50,0 - 30,0 °C	400,0 V	
Werkstoff Pumpe	Baujahr	
Sphäroguss JS 1025	2009	
Werkstoff Lager	Schutzart	
Chromstahl 1.4021/Kohle	IP64/IP55	
Prüfdatum	Prüfer	Isol. Kl.
12.02.2009	K	H
HERMETIC-Pumpen GmbH D-79194 Gundelfingen		