

Bitzer 4N-20.2

Specifications

Бренд	Bitzer
Тип	4N-20.2
Хладагент	Freon
kW at -5°C/+40°C	38,1
кВт at -10°C/+40°C	31,3
кВт at -20°C/+40°C	20,4
кВт at -30°C/+40°C	12,4
кВт at -40°C/+40°C	6,7
Электродвигатель	380-420 V - 50 Hz - 1450
Specs	RPM - 37 A - 19,5 kW
Разгруженный старт	✓
Управление	✓
производительностью	
На стальной раме	✓
Прессостаты	✓
Жидкостный ресивер	✓
Жидкостный ресивер л.30	
Маслоотделитель	✓
Фильтр-осушитель	✓
Смотровое стекло	✓
m3 / h	56,1
Package / Rack	✓
Размеры	1560x1040x990 mm (LxWxH)
Stock	1



Description

Used Bitzer 4N-20.2

Used Bitzer 4N-20.2 semi-hermetic reciprocating compressor. Complete with 30 ltr Bitzer F 300 H liquid receiver, liquid line filter dryer, muffler, Temprite oil separator and pressure switches. The compressor is capacity controlled and has a unloaded start. *Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *Optional we can also perform a new paint job and arrange the logistics.



