

# Bitzer 6H-25.2Y-40P

## Specifications

|                    |                             |
|--------------------|-----------------------------|
| Бренд              | Bitzer                      |
| Тип                | 6H-25.2Y-40P                |
| Хладагент          | Freon                       |
| Refrigerant type   | Freon                       |
| kW at -5°C/+40°C   | 74,7                        |
| кВт at -10°C/+40°C | 61,6                        |
| кВт at -20°C/+40°C | 40,4                        |
| кВт at -30°C/+40°C | 24,8                        |
| кВт at -40°C/+40°C | 13,4                        |
| На стальной раме   | ✓                           |
| Прессостаты        | ✓                           |
| Манометры          | ✓                           |
| Жидкостный ресивер | ✓                           |
| Маслоотделитель    | ✓                           |
| Фильтр-осушитель   | ✓                           |
| Смотровое стекло   | ✓                           |
| Соленоидный клапан | ✓                           |
| Панель управления  | ✓                           |
| m <sup>3</sup> / h | 110,5 - 133,4               |
| Примечания         | Y.o.b. 2009                 |
| Размеры            | 1650x870x1650 mm<br>(LxWxH) |
| Stock              | 1                           |



## Description

### Used Bitzer 6H-25.2Y-40P

Used Bitzer 6H-25.2Y-40P semi-hermetic reciprocating compressor on Freon. Complete with a Bitzer F732N liquid receiver with a volume of 73 liter, oil separator, liquid line filter drier, pressure and safety switches and a control panel. The compressor has a displacement of 110,5 m<sup>3</sup>/h at 1450 RPM and 133,4 m<sup>3</sup>/h at 1750 RPM.

\*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

\*Optional we can also perform a new paint job and arrange the logistics.



