

Bitzer 6G-40.2 Y condensing unit

Specifications

Бренд	Bitzer
Тип	6G-40.2 Y condensing unit
Хладагент	Freon
kW at 0°C/+40°C	102,6
kW at -5°C/+40°C	85,4
кВт at -10°C/+40°C	70,3
кВт at -20°C/+40°C	46,0
кВт at -30°C/+40°C	28,0
кВт at -40°C/+40°C	14,9
Управление	✓
производительностью	
На стальной раме	✓
Прессостаты	✓
Манометры	✓
Жидкостный ресивер	✓
Жидкостный ресивер л.89 l	
Фильтр-осушитель	✓
Смотровое стекло	✓
Панель управления	✓
m ³ / h	50 Hz - 126,8 m ³ /h / 60 Hz - 152,9 m ³ /h
Примечания	Y.o.b. 2000
Condensing Unit	✓
Размеры	6050x1200x1420 mm (LxWxH)
Stock	1



Description

Used Bitzer 6G-40.2 Y condensing unit

Used condensing unit on Freon. Complete with a Bitzer 6G-40.2 Y semi-hermetic reciprocating compressor, condenser with 3 Sud-Electric SEA-T 265-6 fans - 50 Hz -0,7 kW - 870 RPM - diameter of 630 mm, Bitzer F 902 N liquid receiver with a volume of 89 liters, liquid line filter drier, pressure and safety switches/gauges and control panel with Siemens display. The compressor has a displacement of 126,8 m³/h at 50 Hz and 152,9 m³/h at 60 Hz.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *Optional we can also



perform a new paint job and arrange
the logistics.



Typ 6G-40.2 Y
S.Nr. 15871834

BITZER KÜHLMASCHINENBAU GMBH
Made in E.C.

Nennspannung V 3Ph~	Frequ. Hz	Betr. strom A (max.)	Anlaufstrom A (Y)	A (YY)	Fördervol m³/h	Drehzahl min⁻¹
380-420	50	78	180	323	126.8	1450
440-480	60	78	180	323	152.9	1750

IP 54 | ND/HD max.19 /28 bar|
378 028-05

CE



