

# Sabroe SMC 116L HP

## Specifications

|                     |  |
|---------------------|--|
| Бренд               | Sabroe                                     |
| Тип                 | SMC 116L HP                                |
| Хладагент           | NH 3 (ammonia)                             |
| кВт at +10°C/+40°C  | 1434,8*                                    |
| kW at 0°C/+40°C     | 949,0                                      |
| kW at -5°C/+40°C    | 755,1                                      |
| кВт at -10°C/+40°C  | 590,2                                      |
| Управление          | ✓  |
| производительностью |  |
| На стальной раме    | ✓  |
| Прессостаты         | ✓  |
| Манометры           | ✓  |
| Маслоотделитель     | ✓  |
| Смотровое стекло    | ✓  |
| Панель управления   | ✓  |
| m <sup>3</sup> / h  | 1118 m <sup>3</sup> /h - 1480 RPM          |
| Примечания          | Y.o.b. 1992                                |
| Примечания          | *Capacity based on a bigger electric motor |
| Package / Rack      | ✓  |
| Размеры             | 4700x2600x2300 mm<br>(LxWxH)               |
| Stock               | 1  |



## Description

### Used Sabroe SMC 116L HP

Used Sabroe SMC 116L HP reciprocating compressor on R717 (Ammonia). Complete with a Schorch electric motor - 50/60 Hz - 200/230 kW - 1480/1780 RPM, Lohenner GmbH & Co. with a volume of 1090 liters, Sabroe OVUR 4107 D oil separator, 2 heat exchangers, pressure and safety switches/gauges and Sabroe Unisab RT-control panel. The compressor has a displacement of 1118 m<sup>3</sup>/h at 1480 RPM.

\*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty, and industrial cleaning. \*Optional we can also perform a new paint job and arrange the logistics.









