

Bitzer 4H.2 / 6G.2 / 6F.2

Specifications

Бренд	Bitzer
Тип	4H.2 / 6G.2 / 6F.2
Хладагент	Freon
кВт at -10°C/+40°C	190
кВт at -20°C/+40°C	124,5
кВт at -30°C/+40°C	76,2
кВт at -40°C/+40°C	41,5
Электродвигатель	16 / 30 / 37
Specs	
Разгруженный старт	✓
На стальной раме	✓
Прессостаты	✓
Манометры	✓
Жидкостный ресивер	✓
Жидкостный ресивер л.20	
Маслоотделитель	✓
Фильтр-осушитель	✓
Панель управления	✓
Примечания	# // Electromotor 16 kW at 1445 RPM (4H.2) // 30 kW at 1475 RPM (6H.2) // 37 kW at 1480 RPM (6F.2) // Evaporator Helpman PLV 24-4
Примечания	R404a – R22 or other freon types



	(LxWxH)
Вазы	3900x1700x2500 mm

Description

Used Bitzer 4H.2 / 6G.2 / 6F.2

Used Bitzer 4H.2 / 6G.2 / 6F.2 freon compressor rack, complete with unloaded start, pressure safety switches, pressure gauges, oil separator, liquid line filter drier, control panel and liquid receiver with a volume of 20 liters.

Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and deliver after an industrial cleaning. *If requested we are happy to arrange your logistics.







