

Bitzer 4P.2 (x2)

Specifications

Бренд	Bitzer
Тип	4P.2 (x2)
Хладагент	Freon
кВт at +10°C/+40°C	103,8
kW at 0°C/+40°C	79,2
kW at -5°C/+40°C	60,4
кВт at -10°C/+40°C	49,6
кВт at -20°C/+40°C	32,1
кВт at -30°C/+40°C	19,4
кВт at -40°C/+40°C	10,4
Электродвигатель	11
Спес	
Разгруженный старт	✓
На стальной раме	✓
Прессостаты	✓
Манометры	✓
Жидкостный ресивер	✓
Жидкостный ресивер л.80	
Маслоотделитель	✓
Фильтр-осушитель	✓
Смотровое стекло	✓
Панель управления	✓
Примечания	Electromotor: 11 kW at 1460 RPM
Примечания	R404a - R22 or other freon types
Package / Rack	✓



Размеры	2400x1300x2150 mm (LxWxH)
Stock	1

Description

Used Bitzer 4P.2 (x2)

Used Bitzer 4P.2 (x2) freon compressor rack, complete with unloaded start, pressure safety switches, pressure gauges, oil separator, liquid line filter drier, sight glass, control panel and liquid receiver with a volume of 80 liters.

Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and deliver after an industrial cleaning. *If requested we are happy to arrange your logistics.



