

## York / Frick 8 X F 880

### Specifications

Бренд	York / Frick
Тип	8 X F 880
Хладагент	Freon
кВт at +10°C/+40°C	343
kW at 0°C/+40°C	231
кВт at -10°C/+40°C	139
Stock	1



### Description

#### Used York / Frick 8 X F 880

Used York / Frick 8 X F 880 single stage piston compressor \*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. \*Optional we can also perform a new paint job and arrange the logistics.



<b>R 22</b>	<b>COMPRESSEUR SIMPLE ETAGE MODELE 8 XF 88.1</b>	<b>88.1</b>
-------------	--	-------------

Puissance frigorifique en kW  
Puissance absorbée sur l'arbre en kW

Fluide frigorigène : R 22  
Vitesse de rotation : 1450 tr/m  
Volume engendré : 317,6 m<sup>3</sup>

Température saturante d'aspiration en °C (To)

	18	16	14	12	10	8	6	4	2	0	-2	-4	-6	-8	-10
54	387	361	336	312	289	267	247	228	209	191	173	156	141	127	114
52	396	370	344	320	297	275	254	234	215	197	178	161	145	131	117
50	406	379	353	328	304	282	261	241	221	202	183	166	150	134	121
48	415	388	362	336	312	289	268	247	227	208	188	170	154	138	124
46	424	397	370	344	320	297	274	254	233	214	194	175	158	142	128
44	433	405	379	353	328	304	281	260	240	219	199	180	163	146	131
42	442	414	387	361	335	311	288	267	246	225	204	185	167	150	135
40	451	423	395	369	343	319	295	273	252	231	210	190	172	154	139
38	460	431	404	377	351	326	302	280	258	237	215	195	176	159	143
36	468	439	412	385	358	333	309	287	265	243	220	200	181	163	146
34	477	448	420	392	366	341	316	293	271	249	226	205	185	167	150
32		456	427	400	373	348	323	300	277	255	232	210	190	171	154
30			435	407	381	355	330	307	284	261	237	215	195	176	158

Humidification  
nécessaire  
dans la zone  
ombrée