

Bitzer 4H.2 Condensing unit

Specifications

Brand	Bitzer
Type	4H.2 Condensing unit
Refrigerant	Freon
kW at 0°C/+40°C	60,0
kW at -5°C/+40°C	50,0
kW at -10°C/+40°C	41,2
kW at -20°C/+40°C	27,1
kW at -30°C/+40°C	16,7
kW at -40°C/+40°C	9,2
kW at -45°C/+40°C	6,4
Electromotor Specs	50 Hz - 11 kW - 965 RPM
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Liquid receiver	✓
Liquid receiver ltr.	52
Liquid line filter drier	✓
Sight Glass	✓
m3 / h	88,0
Condensing Unit	✓
Sizes	1950x750x1890 mm (LxWxH)
Stock	1



Description

Used Bitzer 4H.2 Condensing unit

Used Bitzer 4H.2 condensing unit on Freon. Complete with 1 Bitzer 4T.2 open-type reciprocating compressor, condenser with 6 fans - 50 Hz - 0,3 kW - 1390 RPM and a diameter of 380 mm, Rotor XKF 160L06 806H elektromotor: 50 Hz - 11 kW - 965 RPM, Apparatebau liquid receiver with a volume of 52 liters, liquid line filter drier, pressure and safety switch and a control box. *Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we solely deliver our orders after performing an extensive test and an industrial cleaning. If requested we are happy to arrange your logistics.





