

Bitzer LHV6/4EC-6.F1Y-40S / 4EC-6.F1Y-40S Condensing unit

Specifications

Brand	Bitzer
Type	LHV6/4EC-6.F1Y-40S / 4EC-6.F1Y-40S Condensing unit
Refrigerant	Freon
kW at -10°C/+40°C	15,1
kW at -20°C/+40°C	10,4
kW at -30°C/+40°C	6,3
kW at -40°C/+40°C	3,2
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Liquid receiver	✓
Liquid receiver ltr.	18
Liquid line filter drier	✓
Sight Glass	✓
Control panel	✓
m ³ / h	22,7
Remarks	Y.o.b. 2011
Weight in kg.	295
Sizes	1470x610x1460 mm (LxWxH)
Stock	1



Description

Used Bitzer LHV6/4EC-6.F1Y-40S / 4EC-6.F1Y-40S Condensing unit

Used Bitzer LHV6/4EC-6.F1Y / 4EC-6.F1Y-40S condensing unit on Freon. Complete with 1 Bitzer 4EC-6.F1Y-40S semi-hermetic reciprocating compressor, condenser with 2 Ziehl-Abegg fans - 50 Hz - 0,41 kW - 1320 RPM - diameter 450 mm and a total airflow of 8.400 m³/h, Bitzer FS188 liquid receiver with a volume of 18 liter, liquid line filter drier, pressure and safety switch and a Bitzer control display.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we solely deliver our orders after performing an extensive test and an industrial




cleaning. If requested we are happy to
arrange your logistics.



RC_ALDI_CHAM_GDC/+3

Ref. : GROUPE DE CONDENSATION
BITZER LHV6/4EC-6.F1Y-40S
Centrale Frigorifique Positive 3



Type de fluide : R - 449A

Quantité : kg

Groupe de fluide : 2

Groupe de sécurité : A1

GWP :

Equivalence CO2 : T

Hermétiquement scellé :
 OUI NON



Bitzer

Typ 4EC-6.F1Y-40S
S.Nr. 1680115969

BITZER KÜHLMASCHINENBAU GMBH
Made in E.C.



Nennspannung	Frequ.	Max.Betr.strom	Anlaufstrom	Fördervol.	Drehzahl
V Δ 3Ph~ V Y 3Ph~	Hz	A(Δ) A(Y)	A(Δ) A(Y)	m³/h	min ⁻¹
220-240	380-420	50 22,9 13,2	107,7 62,2	22,7	1450
265-290	440-480	60 22,9 13,2	107,7 62,2	27,4	1750

IP 65 ND/HD max. 19 / 28 bar



37822605

