

Bock HGX6/1240-4 S (x1) & HGX6/1410-4 S (x1)

Specifications

Brand	Bock
Type	HGX6/1240-4 S (x1) & HGX6/1410-4 S (x1)
Refrigerant	Freon
kW at +10°C/+40°C	171,3
kW at 0°C/+40°C	115,1
kW at -5°C/+40°C	92,6
kW at -10°C/+40°C	73,4
kW at -20°C/+40°C	43,8
kW at -30°C/+40°C	23,9
Unloaded Start	✓
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	✓
Hp/Lp/Op	
Condensing pressure switches	✓
Oil separator	✓
Oil level system AC&R	✓
Sight Glass	✓
Solenoid Valve	✓
m ³ / h	230,0
Package / Rack	✓



(LxWxH)

Size

1680x1440x1460 mm

Description

Used Bock HGX6/1240-4 S (x1) & HGX6/1410-4 S (x1)

Used Bock HGX6/1240-4 S (x1) & Bock HGX6/1410-4 S (x1) semi-hermetic reciprocating compressor rack. Complete with a AC&R S-1903 oil separator, oil reservoir and pressure and safety switches/gauges. The compressors have a displacement of 230 m³/h. Capacity based on the use of Freon type: R134a.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *Optional we can also perform a new paint job and arrange the logistics.





