

## Bitzer 6F.2

### Specifications

|                          |                                                                          |
|--------------------------|--------------------------------------------------------------------------|
| Brand                    | Bitzer                                                                   |
| Type                     | 6F.2                                                                     |
| Refrigerant              | Freon                                                                    |
| kW at 0°C/+40°C          | 127,4                                                                    |
| kW at -5°C/+40°C         | 105,7                                                                    |
| kW at -10°C/+40°C        | 87,0                                                                     |
| kW at -20°C/+40°C        | 56,7                                                                     |
| kW at -30°C/+40°C        | 34,4                                                                     |
| Unloaded Start           | ✓                                                                        |
| Pressure safety switches | ✓                                                                        |
| Hp/Lp/Op                 |                                                                          |
| Oil level system AC&R    | ✓                                                                        |
| Sight Glass              | ✓                                                                        |
| Solenoid Valve           | ✓                                                                        |
| m <sup>3</sup> / h       | 94,1 m <sup>3</sup> /h at 900 RPM &<br>183 m <sup>3</sup> /h at 1750 RPM |
| Sizes                    | 1480x770x700 mm<br>(LxWxH)                                               |
| Stock                    | 1                                                                        |



### Description

#### Used Bitzer 6F.2

Used Bitzer 6F.2 open-type reciprocating compressor on Freon. Complete with a electric motor - 50 Hz - 30 kW - 1477 RPM, AC&R oil level system, pressure and safety switches. The compressor has a displacement of 94,1 m<sup>3</sup>/h at 900 RPM & 183 m<sup>3</sup>/h at 1750 RPM.

\*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment solely if it has passed our extensive test. Warranty and industrial cleaning are included in your purchase. \*If requested we are happy to arrange your shipment.





