

Bitzer 2U-5.2 Water cooled condensing unit

Specifications

| | |
|--------------------------|-------------------------------------|
| Brand | Bitzer |
| Type | 2U-5.2 Water cooled condensing unit |
| Refrigerant | Freon |
| kW at 0°C/+40°C | 15,2 |
| kW at -5°C/+40°C | 12,6 |
| kW at -10°C/+40°C | 10,3 |
| kW at -20°C/+40°C | 6,7 |
| kW at -30°C/+40°C | 4,1 |
| Unloaded Start | ✓ |
| On steel base frame | ✓ |
| Pressure safety switches | ✓ |
| Hp/Lp/Op | |
| Pressure gauges | ✓ |
| Hp/Lp/Op | |
| Liquid receiver | ✓ |
| Liquid line filter drier | ✓ |
| Sight Glass | ✓ |
| Solenoid Valve | ✓ |
| Control panel | ✓ |
| m ³ / h | 18,6 m ³ /h |
| Condensing Unit | ✓ |
| Sizes | 1200x820x920 mm (LxWxH) |
| Stock | 1 |



Description

Used Bitzer 2U-5.2 Water cooled condensing unit

Used water cooled condensing unit on Freon. Complete with a Bitzer 2U-5.2 semi-hermetic reciprocating compressor, Bitzer K202 HB shell and tube condenser, liquid receiver, pressure and safety switches/gauges and a control cabinet. The compressor has a displacement of 18,6 m³/h.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment solely if it has passed our extensive test. Warranty and industrial cleaning are included in your purchase.

*If requested we are happy to arrange your shipment.





