

Helpman HTC 100-122-V/ 420 PREP

Specifications

Brand	Helpman
Type	HTC 100-122-V/ 420 PREP
Product type	Drycooler
kW	133,7*
Number of Fans	2
RPM of the Fans	420/310
Refrigerant	Glycol
Air Flow in m ³ /h	38.000
diameter fans Ø	1000 mm
Surface (m ²)	304
Tube volume	25 dm ³
Sizes	4150x1250x1450 mm (LxWxH)
Weight	502 kg
Remarks	Y.o.b. 2002
Remarks	*Capacity is based on a medium inlet temperature of 60°C and an outlet temperature of 40°C
Stock	1



Description

Used Helpman HTC 100-122-V/ 420 PREP

Used Helpman HTC 100-122-V drycooler. Complete with 2 Ziehl-Abegg FE100-NDS.6N.V7 fans - 50 Hz - 0,87/0,49 kW - 430/310 RPM - diameter 1000 mm and a total airflow of 38.000 m³/h.

The current condenser will be converted into a drycooler and the appropriate flanges will be installed. The drycooler has a capacity of 133,7kW with a medium inlet temperature of 60°C and an outlet temperature of 40°C.

*All components of this used condenser will be tested on adequate functionality, leak free condition (electro engines), condensing block,



bearings. Choosing HOSBV means buying with warranty. We perform an industrial cleaning on demand, we can arrange your shipment.



HELPMAN		Apparatenfabriek Helpman B.V.	
		Peizerweg 97, 9727 AJ Groningen (NL)	
		Tel. ++31 50 5217555 / Fax ++31 50 5264873	
		info@helpman.com / www.helpman.com	
Type	HTC 100.122-V/420 PREP		
Serial number	511292/120964-15944/01		
Refrigerant	R404A		
Operating temp.	100	°C (min/max)	
Design/test pressure	22/28	bar	year 2002
Internal volume	25.0	dm ³	
Weight (empty)	502	kg	0134 CE



