

# Bitzer 4NES-20Y-40P

## Specifications

|                          |  |
|--------------------------|--|
| Brand                    | Bitzer   |
| Type                     | 4NES-20Y-40P   |
| Refrigerant              | Freon  |
| kW at 0°C/+40°C          | 47,2   |
| kW at -5°C/+40°C         | 38,8   |
| kW at -10°C/+40°C        | 31,6   |
| kW at -20°C/+40°C        | 20,1   |
| kW at -30°C/+40°C        | 11,9   |
| kW at -40°C/+40°C        | 6,4  |
| kW at -45°C/+40°C        | 4,3  |
| Capacity Control         | ✓  |
| On steel base frame      | ✓  |
| Pressure safety switches | ✓  |
| Hp/Lp/Op                 |  |
| Liquid receiver          | ✓  |
| Liquid receiver ltr.     | 54   |
| Liquid line filter drier | ✓  |
| Sight Glass              | ✓  |
| Solenoid Valve           | ✓  |
| m <sup>3</sup> / h       | 56,2 m <sup>3</sup> /h at 50 Hz &<br>67,8 m <sup>3</sup> /h at 60 Hz |
| Remarks                  | Y.o.b. 2017  |
| Sizes                    | 1700x360x720 mm<br>(LxWxH)   |
| Stock                    | 1  |



## Description

### Used Bitzer 4NES-20Y-40P

Used Bitzer 4NES-20Y-40P semi-hermetic reciprocating compressor on Freon. Complete with a Bitzer F552T liquid receiver with a volume of 54 liter, pressure and safety switches, liquid line filter, capacity control and a sight glass. The compressor has a displacement of 56,2 m<sup>3</sup>/h at 50 Hz & 67,8 m<sup>3</sup>/h at 60 Hz.

\*Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we solely deliver our orders after performing an extensive test and an industrial cleaning. If requested we are happy to arrange your logistics.



