

Bitzer HSN 7471-75-40P

Specifications

Brand	Bitzer
Type	HSN 7471-75-40P
Refrigerant	Freon
Refrigerant type	R404A
kW at -20°C/+40°C	120,3
kW at -30°C/+40°C	82,9
kW at -40°C/+40°C	54,5
kW at -45°C/+40°C	43,0
Unloaded Start	✓
Capacity Control	✓
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	✓
Hp/Lp/Op	
Liquid receiver	✓
Liquid receiver ltr.	112
Oil separator	✓
Liquid line filter drier	✓
Sight Glass	✓
Solenoid Valve	✓
m3 / h	250
Remarks	Y.o.b. 2011
Sizes	1900x1050x2030 mm (LxWxH)
Stock	1



Description

Used Bitzer HSN 7471-75-40P

Used Bitzer HSN7471-75-40P semi-hermetic screw compressor Freon on steel base frame. Complete with Bitzer F1202N liquid receiver, Bitzer OA1954 oil separator, Gea GBS 700M-20 brazed heat exchanger as economizer, Gea GBS 700M-44 brazed heat exchanger for heat recovery, pressure and safety switches/gauges and a liquid line filter drier. The compressor has a displacement of 250 m³/h at 2900 RPM and 300 m³/h at 3500 RPM. The capacities are with a economizer.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also perform a new paint job and arrange the logistics.



Refrigeration Support 22

Typ HSN7471-75-40P
S.Nr. 1081101746

SITZER KÜHLMASCHINENBAU GMBH
Made in E.C.

Nennspannung V 3Ph~	Frequ. Hz	Befr.strom A (max)	Anlaufstrom A (Δ)	A (ΔΔ)	Fördervol. m³/h	Drehzahl min⁻¹
380-415	50	144	350	585	250	2900
440-480	60	144	350	585	300	3500

IP 54 ND/HD max : 1/28 bar

CE



